

Certificate of compliance with the order

(according to DIN 50049 - 2.1 / EN 10204 - 2.1

V-00

Batch No.: 161202207

From order No.:

We accept sole responsibility in stating that the product conforms to the presently valid and agreed specifications.

Depth filter sheets are products used in the filtration of liquids for solid/liquid separation.

		Approx. values
Water flow rate Δp 100 kPa	($Lm^{-2} min^{-1}$)	1700
Weight per unit area	(gm^{-2})	1200
Thickness	(mm)	4.3
Ash content	(%)	46
Extractable ions		
soluble in: acetic acid (5%), e. g.	Ca (mgm^{-2})	900
	Fe (mgm^{-2})	15
	Al (mgm^{-2})	30

The tests are carried out as per the methods of the European Association of Depth Filtration e.V. or in accordance with company-specific test procedures.

Heavy metals as per recommendation XXXVI/1 within the Lebensmittel- und Bedarfsgegenstände-gesetz - LMBG - (Foodstuff and other Commodities Act) < 50 ppm

The product conforms to the recommendation XXXVI/1 and meets the requirements of the Lebensmittel- und Bedarfsgegenstände-gesetz - LMBG - (Foodstuff and other Commodities Act) especially §§ 5, 30 and 31. It may without any reservation be used for cold filtration of foodstuffs.

Main components: cellulose
natural diatomaceous earth
perlite

Components < 3 %: additives corresponding to the recommendation XXXVI polyolefine fibres

Safe filtration requires that all process parameters relevant to a special application have been validated. The above statements do not rescind from the obligation to perform an incoming goods control. All above information are based on our present state of knowledge and do not claim to be complete. The use resp. handling of our products is in the buyer's responsibility also with regard to possible protective rights of third parties.

Bad Kreuznach, 26-Jul-06

Name of contact person of In. VIA
-Factory Expert-

This Dokument has been made by computer and is valid without a signature.

Certificate of compliance with the order

(according to DIN 50049 - 2.1 / EN 10204 - 2.1

V-01

Batch No.: 172201207

From order No.:

We accept sole responsibility in stating that the product conforms to the presently valid and agreed specifications.

Depth filter sheets are products used in the filtration of liquids for solid/liquid separation.

		Approx. values
Water flow rate Δp 100 kPa	(Lm ² min ⁻¹)	1275
Weight per unit area	(gm ²)	1250
Thickness	(mm)	4.1
Ash content	(%)	46
Extractable ions		
soluble in: acetic acid (5%), e. g.	Ca (mgm ⁻²)	900
	Fe (mgm ⁻²)	15
	Al (mgm ⁻²)	30

The tests are carried out as per the methods of the European Association of Depth Filtration e.V. or in accordance with company-specific test procedures.

Heavy metals as per recommendation XXXVI/1 within the Lebensmittel- und Bedarfsgegenständegesetz - LMBG - (Foodstuff and other Commodities Act) **< 50 ppm**

The product conforms to the recommendation XXXVI/1 and meets the requirements of the Lebensmittel- und Bedarfsgegenständegesetz - LMBG - (Foodstuff and other Commodities Act) especially §§ 5, 30 and 31. It may without any reservation be used for cold filtration of foodstuffs.

<u>Main components:</u>	cellulose natural diatomaceous earth perlite	<u>Components < 3 %:</u>	additives corresponding to the recommendation XXXVI polyolefine fibres
-------------------------	--	-----------------------------	---

Safe filtration requires that all process parameters relevant to a special application have been validated. The above statements do not rescind from the obligation to perform an incoming goods control. All above information are based on our present state of knowledge and do not claim to be complete. The use resp. handling of our products is in the buyer's responsibility also with regard to possible protective rights of third parties.

Bad Kreuznach, 26-Jul-06

Name of contact person of In. VIA
-Factory Expert-

This Dokument has been made by computer and is valid without a signature.

Batch No.: 172201206

From order No.:

We accept sole responsibility in stating that the product conforms to the presently valid and agreed specifications.

Depth filter sheets are products used in the filtration of liquids for solid/liquid separation.

		Approx. values
Water flow rate Δp 100 kPa	($Lm^{-2} min^{-1}$)	925
Weight per unit area	(gm^{-2})	1250
Thickness	(mm)	4.1
Ash content	(%)	46
Extractable ions		
soluble in: acetic acid (5%), e. g.		
	Ca (mgm^{-2})	900
	Fe (mgm^{-2})	15
	Al (mgm^{-2})	50

The tests are carried out as per the methods of the European Association of Depth Filtration e.V. or in accordance with company-specific test procedures.

Heavy metals as per recommendation XXXVI/1 within the Lebensmittel- und Bedarfsgegenständegesetz - LMBG - (Foodstuff and other Commodities Act) **< 50 ppm**

The product conforms to the recommendation XXXVI/1 and meets the requirements of the Lebensmittel- und Bedarfsgegenständegesetz - LMBG - (Foodstuff and other Commodities Act) especially §§ 5, 30 and 31. It may without any reservation be used for cold filtration of foodstuffs.

Main components: cellulose
natural diatomaceous earth
perlite

Components < 3 %: additives corresponding to the recommendation XXXVI polyolefine fibres

Safe filtration requires that all process parameters relevant to a special application have been validated. The above statements do not rescind from the obligation to perform an incoming goods control. All above information are based on our present state of knowledge and do not claim to be complete. The use resp. handling of our products is in the buyer's responsibility also with regard to possible protective rights of third parties.

Bad Kreuznach, 26-Jul-06

Name of contact person of In. VIA
-Factory Expert-

This Dokument has been made by computer and is valid without a signature.

Certificate of compliance with the order

(according to DIN 50049 - 2.1 / EN 10204 - 2.1

V-03**Batch No.: 173201208****From order No.:**

We accept sole responsibility in stating that the product conforms to the presently valid and agreed specifications.

Depth filter sheets are products used in the filtration of liquids for solid/liquid separation.

		Approx. values
Water flow rate Δp 100 kPa	($Lm^{-2} min^{-1}$)	785
Weight per unit area	(gm^{-2})	1250
Thickness	(mm)	4.2
Ash content	(%)	46
Extractable ions		
soluble in: acetic acid (5%), e. g.	Ca (mgm^{-2})	950
	Fe (mgm^{-2})	15
	Al (mgm^{-2})	50

The tests are carried out as per the methods of the European Association of Depth Filtration e.V. or in accordance with company-specific test procedures.

Heavy metals as per recommendation XXXVI/1 within the Lebensmittel- und Bedarfsgegenständegesetz - LMBG - (Foodstuff and other Commodities Act) **< 50 ppm**

The product conforms to the recommendation XXXVI/1 and meets the requirements of the Lebensmittel- und Bedarfsgegenständegesetz - LMBG - (Foodstuff and other Commodities Act) especially §§ 5, 30 and 31. It may without any reservation be used for cold filtration of foodstuffs.

Main components: cellulose
natural diatomaceous earth
perlite

Components < 3 %: additives corresponding to the recommendation XXXVI
polyolefine fibres

Safe filtration requires that all process parameters relevant to a special application have been validated. The above statements do not rescind from the obligation to perform an incoming goods control. All above information are based on our present state of knowledge and do not claim to be complete. The use resp. handling of our products is in the buyer's responsibility also with regard to possible protective rights of third parties.

Bad Kreuznach, 26-Jul-06

Name of contact person of In. VIA
-Factory Expert-

This Dokument has been made by computer and is valid without a signature.

Certificate of compliance with the order

(according to DIN 50049 - 2.1 / EN 10204 - 2.1)

V-04**Batch No.: 187203209****From order No.: 101106984**

We accept sole responsibility in stating that the product conforms to the presently valid and agreed specifications.

Depth filter sheets are products used in the filtration of liquids for solid/liquid separation.

		Approx. values
Water flow rate Δp 100 kPa	($Lm^{-2} min^{-1}$)	510
Weight per unit area	(gm^{-2})	1250
Thickness	(mm)	4.0
Ash content	(%)	46
Extractable ions		
soluble in: acetic acid (5%), e. g.	Ca (mgm^{-2})	1000
	Fe (mgm^{-2})	15
	Al (mgm^{-2})	50

The tests are carried out as per the methods of the European Association of Depth Filtration e.V. or in accordance with company-specific test procedures.

Heavy metals as per recommendation XXXVI/1 within the Lebensmittel- und Bedarfsgegenständegesetz - LMBG - (Foodstuff and other Commodities Act) **< 50 ppm**

The product conforms to the recommendation XXXVI/1 and meets the requirements of the Lebensmittel- und Bedarfsgegenständegesetz - LMBG - (Foodstuff and other Commodities Act) especially §§ 5, 30 and 31. It may without any reservation be used for cold filtration of foodstuffs.

<u>Main components:</u>	cellulose natural diatomaceous earth perlite	<u>Components < 3 %:</u>	additives corresponding to the recommendation XXXVI polyolefine fibres
-------------------------	--	-----------------------------	---

Safe filtration requires that all process parameters relevant to a special application have been validated. The above statements do not rescind from the obligation to perform an incoming goods control. All above information are based on our present state of knowledge and do not claim to be complete. The use resp. handling of our products is in the buyer's responsibility also with regard to possible protective rights of third parties.

Bad Kreuznach, 26-Okt-07

Name of contact person of In. VIA

- Factory Expert

28100 ALCOBENDAS - MADRID

This Dokument has been made by computer and is valid without a signature.

Certificate of compliance with the order

(according to DIN 50049 - 2.1 / EN 10204 - 2.1

V-05

Batch No.: 174201203

From order No.:

We accept sole responsibility in stating that the product conforms to the presently valid and agreed specifications.

Depth filter sheets are products used in the filtration of liquids for solid/liquid separation.

		Approx. values
Water flow rate Δp 100 kPa	(Lm ² min ⁻¹)	213
Weight per unit area	(gm ⁻²)	1350
Thickness	(mm)	3.9
Ash content	(%)	46
Extractable ions soluble in: acetic acid (5%), e. g.		
Ca	(mgm ⁻²)	1350
Fe	(mgm ⁻²)	15
Al	(mgm ⁻²)	80

The tests are carried out as per the methods of the European Association of Depth Filtration e.V. or in accordance with company-specific test procedures.

Heavy metals as per recommendation XXXVI/1 within the
Lebensmittel- und Befarfsgegenständegesetz - LMBG - (Foodstuff and
other Commodities Act)

< 50 ppm

The product conforms to the recommendation XXXVI/1 and meets the requirements of the Lebensmittel- und Befarfsgegenständegesetz - LMBG - (Foodstuff and other Commodities Act) especially §§ 5, 30 and 31. It may without any reservation be used for cold filtration of foodstuffs.

Main components: cellulose
natural diatomaceous earth
perlite

Components < 3 %: additives corresponding to the
recommendation XXXVI
polyolefine fibres

Safe filtration requires that all process parameters relevant to a special application have been validated. The above statements do not rescind from the obligation to perform an incoming goods control. All above information are based on our present state of knowledge and do not claim to be complete. The use resp. handling of our products is in the buyer's responsibility also with regard to possible protective rights of third parties.

Bad Kreuznach, 26-Jul-06

Name of contact person of In. VIA
-Factory Expert-

This Dokument has been made by computer and is valid without a signature.

Certificate of compliance with the order

(according to DIN 50049 - 2.1 / EN 10204 - 2.1

V-07

Batch No.: 173201205 / 173205207

From order No.:

We accept sole responsibility in stating that the product conforms to the presently valid and agreed specifications.

Depth filter sheets are products used in the filtration of liquids for solid/liquid separation.

		Approx. values
Water flow rate Δp 100 kPa	($Lm^{-2} min^{-1}$)	185
Weight per unit area	(gm^{-2})	1350
Thickness	(mm)	3.9
Ash content	(%)	46
Extractable ions		
soluble in: acetic acid (5%), e. g.		
	Ca (mgm^{-2})	1400
	Fe (mgm^{-2})	15
	Al (mgm^{-2})	80

The tests are carried out as per the methods of the European Association of Depth Filtration e.V. or in accordance with company-specific test procedures.

Heavy metals as per recommendation XXXVI/1 within the Lebensmittel- und Bedarfsgegenständegesetz - LMBG - (Foodstuff and other Commodities Act) **< 50 ppm**

The product conforms to the recommendation XXXVI/1 and meets the requirements of the Lebensmittel- und Bedarfsgegenständegesetz - LMBG - (Foodstuff and other Commodities Act) especially §§ 5, 30 and 31. It may without any reservation be used for cold filtration of foodstuffs.

Main components: cellulose
natural diatomaceous earth
perlite

Components < 3 %: additives corresponding to the recommendation XXXVI
polyolefine fibres

Safe filtration requires that all process parameters relevant to a special application have been validated. The above statements do not rescind from the obligation to perform an incoming goods control. All above information are based on our present state of knowledge and do not claim to be complete. The use resp. handling of our products is in the buyer's responsibility also with regard to possible protective rights of third parties.

Bad Kreuznach, 26-Jul-06

J. Vosseberg
-Factory Expert-

This Dokument has been made by computer and is valid without a signature.

V-010

Batch No.: 187204202

From order No.: 101106984

We accept sole responsibility in stating that the product conforms to the presently valid and agreed specifications.

Depth filter sheets are products used in the filtration of liquids for solid/liquid separation.

		Approx. values
Water flow rate Δp 100 kPa	($Lm^{-2} min^{-1}$)	146
Weight per unit area	(gm^{-2})	1350
Thickness	(mm)	3.7
Ash content	(%)	46
Extractable ions soluble in: acetic acid (5%), e. g.		
Ca	(mgm^{-2})	1500
Fe	(mgm^{-2})	15
Al	(mgm^{-2})	100

The tests are carried out as per the methods of the European Association of Depth Filtration e.V. or in accordance with company-specific procedures.

Heavy metals as per recommendation XXXVI/1 within the Lebensmittel- und Bedarfsgegenständegesetz - LMBG - (Foodstuff and other Commodities Act) **< 50 ppm**

The product conforms to the recommendation XXXVI/1 and meets the requirements of the Lebensmittel- und Bedarfsgegenständegesetz - LMBG - (Foodstuff and other Commodities Act) especially §§ 5, 30 and 31. It may without any reservation be used for cold filtration of foodstuffs.

<u>Main components:</u>	cellulose natural diatomaceous earth perlite	<u>Components < 3 %:</u>	additives corresponding to the recommendation XXXVI polyolefine fibres
-------------------------	--	-----------------------------	--

Safe filtration requires that all process parameters relevant to a special application have been validated. The above statements do not rescind from the obligation to perform an incoming goods control. All above information are based on our present state of knowledge and do not claim to be complete. The use resp. handling of our products is in the buyer's responsibility also with regard to possible protective rights of third parties.

Bad Kreuznach, 26-Okt-07

Name of contact person **In. VIA**
-Factory Expert

This Dokument has been made by computer and is valid without a signature.

Batch No.: 172201202

From order No.:

We accept sole responsibility in stating that the product conforms to the presently valid and agreed specifications.

Depth filter sheets are products used in the filtration of liquids for solid/liquid separation.

		Approx. values
Water flow rate Δp 100 kPa	($Lm^{-2} min^{-1}$)	93
Weight per unit area	(gm^{-2})	1350
Thickness	(mm)	3.7
Ash content	(%)	46
Extractable ions		
soluble in: acetic acid (5%), e. g.	Ca (mgm^{-2})	1500
	Fe (mgm^{-2})	10
	Al (mgm^{-2})	100

The tests are carried out as per the methods of the European Association of Depth Filtration e.V. or in accordance with company-specific test procedures.

Heavy metals as per recommendation XXXVI/1 within the Lebensmittel- und Bedarfsgegenstände-gesetz - LMBG - (Foodstuff and other Commodities Act) **< 50 ppm**

Bacteria retention capability with *Serratia marcescens*:
LRV (Log Reduction Value) **6.5**
(according to the method of the European Association of Depth Filtration e.V.)

The product conforms to the recommendation XXXVI/1 and meets the requirements of the Lebensmittel- und Bedarfsgegenstände-gesetz - LMBG - (Foodstuff and other Commodities Act) especially §§ 5, 30 and 31. It may without any reservation be used for cold filtration of foodstuffs.

Main components: cellulose
natural diatomaceous earth
perlite

Components < 3 %: additives corresponding to the recommendation XXXVI
polyolefine fibres

Safe filtration requires that all process parameters relevant to a special application have been validated. The above statements do not rescind from the obligation to perform an incoming goods control. All above information are based on our present state of knowledge and do not claim to be complete. The use resp. handling of our products is in the buyer's responsibility also with regard to possible protective rights of third parties.

Bad Kreuznach, 26-Jul-06

Name of contact person of In. VIA
-Factory Expert-

This Dokument has been made by computer and is valid without a signature.

Batch No.: 173206200

From order No.:

We accept sole responsibility in stating that the product conforms to the presently valid and agreed specifications.

Depth filter sheets are products used in the filtration of liquids for solid/liquid separation.

		Approx. values
Water flow rate Δp 100 kPa	($Lm^{-2} min^{-1}$)	68
Weight per unit area	(gm^{-2})	1400
Thickness	(mm)	3.8
Ash content	(%)	46
Extractable ions soluble in: acetic acid (5%), e. g.		
	Ca (mgm^{-2})	1750
	Fe (mgm^{-2})	10
	Al (mgm^{-2})	100

The tests are carried out as per the methods of the European Association of Depth Filtration e.V. or in accordance with company-specific test procedures.

Heavy metals as per recommendation XXXVI/1 within the Lebensmittel- und Bedarfsgegenständegesetz - LMBG - (Foodstuff and other Commodities Act) **< 50 ppm**

Bacteria retention capability with *Serratia marcescens*:
LRV (Log Reduction Value) **7**
(according to the method of the European Association of Depth Filtration e.V.)

The product conforms to the recommendation XXXVI/1 and meets the requirements of the Lebensmittel- und Bedarfsgegenständegesetz - LMBG - (Foodstuff and other Commodities Act) especially §§ 5, 30 and 31. It may without any reservation be used for cold filtration of foodstuffs.

Main components: cellulose
natural diatomaceous earth
perlite

Components < 3 %: additives corresponding to the recommendation XXXVI
polyolefine fibres

Safe filtration requires that all process parameters relevant to a special application have been validated. The above statements do not rescind from the obligation to perform an incoming goods control. All above information are based on our present state of knowledge and do not claim to be complete. The use resp. handling of our products is in the buyer's responsibility also with regard to possible protective rights of third parties.

Bad Kreuznach, 26-Jul-06

Name of contact person of In. VIA
-Factory Expert-

This Dokument has been made by computer and is valid without a signature.

Certificate of compliance with the order

(according to DIN 50049 - 2.1 / EN 10204 - 2.1

V-014

Batch No.: 187204204

From order No.: 101106984

We accept sole responsibility in stating that the product conforms to the presently valid and agreed specifications.

Depth filter sheets are products used in the filtration of liquids for solid/liquid separation.

Approx. values

Water flow rate Δp 100 kPa	($Lm^{-2} min^{-1}$)	41
Weight per unit area	(gm^{-2})	1450
Thickness	(mm)	3.8
Ash content	(%)	51
Extractable ions		
soluble in: acetic acid (5%), e. g.	Ca (mgm^{-2})	2000
	Fe (mgm^{-2})	15
	Al (mgm^{-2})	100

The tests are carried out as per the methods of the European Association of Depth Filtration e.V. or in accordance with company-specific test procedures.

Heavy metals as per recommendation XXXVII/1 within the Lebensmittel- und Bedarfsgegenständegesetz - LMBG - (Foodstuff and other Commodities Act) < 50 ppm

Bacteria retention capability with *Brevundimonas diminuta*:
LRV (Log Reduction Value) 7.5
(according to the method of the European Association of Depth Filtration e.V.)

The product conforms to the recommendation XXXVII/1 and meets the requirements of the Lebensmittel- und Bedarfsgegenständegesetz - LMBG - (Foodstuff and other Commodities Act) especially §§ 5, 30 and 31. It may without any reservation be used for cold filtration of foodstuffs.

Main components: cellulose
natural diatomaceous earth
perlite

Components < 3 %: additives corresponding to the recommendation XXXVI
polyolefine fibres

Safe filtration requires that all process parameters relevant to a special application have been validated. The above statements do not rescind from the obligation to perform an incoming goods control. All above information are based on our present state of knowledge and do not claim to be complete. The use resp. handling of our products is in the buyer's responsibility also with regard to possible protective rights of third parties.

Bad Kreuznach, 26-Okt-07

Name of contact person of In. VIA
-Factory Expert-

This Dokument has been made by computer and is valid without a signature.